



TOP-LOAD IN
OPTIONAL
STAINLESS-STEEL



182 SERIES WITH
SWING-OUT DOOR

ROTO-JET OF AMERICA COMPANY, INC.

19425 SOLEDAD CANYON ROAD, SUITE 317 SANTA CLARITA, CA 91351 USA

PH 661-299-2231 FX 661-299-9239 EM sales@roto-jettoa.com WEB www.roto-jetpartswasher.com



B-SERIES WITH
LAY-DOWN DOOR

STANDARD MODELS OVERALL COMPARISON BULLETIN

STANDARD MODELS	"Top-Load"	"Swing-Out" Door	"Swing-Out" Door	"Swing-Out" Door	"Swing-Out" Door	"Swing-Out" Door	"Swing-Out" Door	"Swing-Out" Door	"Lay-Down" Door	"Swing-Out" Door	"Swing-Out" Door	"Lay-Down" Door	"Swing-Out" Door	"Lay-Down" Door	"Swing-Out" Door	"Lay-Down" Door	"Swing-Out" Door	"Swing-Out" Door
	100	111	121	131	142	142-ST	162	182A	2B	182B	182C	3B	182D	4B	182E	5B	182F	182G
OVERALL HEIGHT	52"	65"	65"	65"	78"	78"	84"	102"	87"	108"	108"	90"	108"	90"	108"	90"	108"	108"
OVERALL WIDTH	40"	52"	52"	52"	60"	60"	72"	76"	66"	80"	88"	80"	96"	86"	110"	100"	115"	120"
OVERALL DEPTH	34"	40"	40"	46"	41"	61"	52"	66"	* 116" / 72"	70"	78"	* 132" / 84"	84"	* 138" / 90"	96"	* 145" / 100"	102"	108"
TURNTABLE DIAMETER	24"	27"	26"	26"	26"	26"	36"	36"	** 38" / 35"	40"	48"	** 50" / 47"	54"	** 56" / 53"	60"	** 66" / 63"	66"	72"
WORKING HEIGHT	18"	32"	32"	32"	40"	40"	42"	54"	36"	60"	60"	38"	60"	36"	60"	36"	60"	60"
LOAD CAPACITY - LBS	300	500	500	500	800	800	1000	1500	1000	2000	2000	1500	2000	2000	2000	2000	2000	2000
SOLUTION CAPACITY - GALS	25	50	50	70	70	125	120	225	180	240	330	275	400	330	500	500	612	725
WASH PUMP - HP	2	3	3	3	5	5	7.5	15	7.5	15	15	10	15	15	20	20	20	20
WASH PUMP CAPACITY - GPM	36	50	50	50	90	90	110	190	110	200	210	180	225	220	270	270	270	270
WASH PUMP - PSI	40	45	45	45	60	60	60	65	60	65	65	60	65	65	65	70	65	65
WASH NOZZLES	9	20	9	9	12	12	15	26	14	28	30	18	32	26	36	82 Impact-2	38	40
TURNTABLE DRIVE - HP	Jet Drive	Jet Drive	1/15	1/15	1/15	1/15	1/15	1/2	1/3	1/2	1/2	1/3	1/2	1/3	1/2	1/2	1/2	1/2
ELECTRIC HEATING - KW	4.5	6	6	6	12	12	12	18	18	18	18	24	36	36	36	54	54	54
POWER	230V/1P/32A	230V/1P/42A	230V/1P/42A	230V/1P/42A	230V/3P/45A	230V/3P/45A	230V/3P/50A	230V/3P/82A	230V/3P/64A	230V/3P/82A	230V/3P/82A	460V/3P/42A	460V/3P/70A	460V/3P/65A	460V/3P/70A	460V/3P/93A	460V/3P/90A	460V/3P/90A
WEIGHT - LBS	530	960	1100	1250	1500	1700	1850	3500	3500	4500	5500	3900	6000	4500	6500	6000	7000	7500

* Open vs Closed Door
** TTable O.D. vs Basket I.D.

* Open vs Closed Door
** TTable O.D. vs Basket I.D.

* Open vs Closed Door
** TTable O.D. vs Basket I.D.

* Open vs Closed Door
** TTable O.D. vs Basket I.D.

LARGER UNITS ARE AVAILABLE!

Some Options & Modifications not available on all units - see individual MODEL BULLETINS

- RINSE STAGE
- BLOW-OFF STAGE
- DRYING STAGE
- VAPOR EXHAUST or SCRUBBING
- ADD RUST INHIBITOR CYCLE
- INCREASE LOAD CAPACITY
- INCREASE / DECREASE WORK HEIGHT
- "MIRROR" IMAGE CONSTRUCTION
- OIL REMOVAL
- SOLUTION FILTERING
- MFG GAS or STEAM HEATING
- STAINLESS-STEEL CONSTRUCTION
- DIGITAL TEMPERATURE CONTROLS
- DIGITAL CYCLE TIMERS
- PLCs & PROGRAMMABLE TEXT DISPLAY RELAY
- HIGH PRESSURE / HIGH HORSEPOWER PUMPS
- OSCILLATING and CUSTOM SPRAY MANIFOLDS
- CUSTOM PARTS RACKS and BASKETS
- "OVERSEAS" VOLTAGES and EXPORT CRATING
- SLUDGE DRAG-OUT CONVEYORS
- "NON-CONTACT" ELECTRIC HEATERS
- ATTACHED "SWING" BOOMS



Top-Load SS Unit



Custom Head Rack 30-Pcs



Vertical-Door Pass Thru



SS Dual-Turntables



Portable "Tunnel" Washer



Agitation-Lift Parts Washer

PLEASE CONTACT OUR SALES ENGINEERING DEPARTMENT FOR A PROMPT AND COURTEOUS QUOTE.

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. NOT RESPONSIBLE FOR ERRORS OR OMISSIONS.