



ROTO-JET OF AMERICA COMPANY, INC.

19425 SOLEDAD CANYON ROAD, SUITE 317 * SANTA CLARITA, CA 91351 * USA
Ph 661-299-2231 * Fx 661-299-9239 * Email sales@roto-jettoa.com * Web www.roto-jettoa.com

MODEL RJ-140

* Shown in optional SS construction
* Dimensions are subject to final unit configuration

SPECIFICATIONS

| | |
|---|-------------------------|
| Height - Lid Closed | 54" |
| Width | 44" |
| Depth | 74" |
| Turntable Diameter | 26" |
| Working Height | 18" |
| Working Load Limit | 800 LBS |
| Solution Capacity | 120 GAL |
| Standard Pump Motor Size | 5 HP |
| Standard Pump Capacity | 90 GPM @ 60 PSI |
| Wash Nozzles | 12 |
| Turntable Drive - Chain w/"Slip" Lock-up protection | 1/15 HP |
| Vapor Exhaust Stack | 6-5/8" |
| Electric Heat | 12 KW |
| Electric Power Requirement 3 Phase 230V / 460V | 3PH 230V-45A / 460V-23A |
| Fresh Water Inlet x Main Tank Drain Outlet | 1/2" NPT x 1" NPT |
| Weight in Pounds | 1,400 |



STANDARD OPTIONS

Part

| | |
|--|-----------|
| Downsize to 3HP 230V 1P/3P Power | 140-09 |
| 5 HP 230V 1 Phase Power 80A | 140-10 |
| 7-1/2 HP 230V 3P Power 50A / 460V 3P Power 26A | 140-11 |
| 7-Day/24-Hour Digital Timer (Heat or Skimmer) | 140-20 |
| Auto-Refill with Inlet Strainer & Low-Water Shut-Off | 140-21 |
| Evaporation Cycle w/ Separate Heat & Low Shut-Off | 140-22 |
| Oil Skimmer 12" SS Disc 60-Min Spring-Wound Timer | 140-23 |
| HD Oil Skimmer 12" SS Disc 60-Min Ele. Dial Timer | 140-48 |
| 15" Small Parts basket | 140-25 |
| SS Thermometer - Probe Type | 140-26 |
| Stainless Steel Wash Nozzles | 140-27 |
| Lower Spray Bar (only w/140-36) | 140-28 |
| 6" HD Permanent Casters | 140-35 |
| Deep Lid (Increases Working Height To 24") | 140-36 |
| Hand Detailing Brush w/Pump | 140-37 |
| Low-Water Auto Shut-Off | 140-38 |
| Bag Filter System #6 x 18 Filter Housing | 140-39 |
| ** Recirc. Rinse Stage - Stand Alone w/Air Pump, Heat, Auto-Divert | 140-44 |
| ** Shop Air Blow-Off Cycle | 140-45 |
| Vapor Exhaust Fan 120 CFM | 140-47 |
| Vapor Exhaust "Mist Scrubber" 3/4 HP 275 CFM | 140-48 |
| Wiring Upgrade | 140-50 |
| ** Digital Cycle Timer (1 req'd per stage) | 140-51 |
| ** Programmable Relay Control w/Text Display (for mult. stages) | 140-51-PR |
| DEMA Injector (Valve) for adding Rust-Inhibitor or Chemical | 140-54 |
| ** Powered Lid Gravity-Close, Auto-Open | 140-55 |
| Deduction for Non-Powered Turntable w/Positioning Lock | 140-56 |
| Pressure Control Valve w/Gauge | 140-85 |

** these options require wiring upgrade part #140-50

Stainless-Steel Construction Available

EFFECTIVE 1-JAN-13 SUBJECT TO CHANGE WITHOUT NOTICE
LOCAL CODE REQUIREMENTS ARE THE RESPONSIBILITY OF THE PURCHASER

PRICING IS CONFIDENTIAL AND NOT FOR PUBLIC DISSEMINATION

MANUFACTURER OF HIGH-SPEED INDUSTRIAL PARTS WASHERS