



ROTO-JET OF AMERICA COMPANY, INC.

19425 SOLEDAD CANYON ROAD, SUITE 317 * SANTA CLARITA, CA 91351 * USA
Ph 661-299-2231 * Fx 661-299-9239 * Email sales@roto-jettoa.com * Web www.roto-jetpartwasher.com

MODEL RJ-140

* Shown in optional SS construction
* Dimensions are subject to final unit configuration



SPECIFICATIONS

Height - Lid Closed	54"
Width	44"
Depth	74"
Turntable Diameter	26"
Working Height	18"
Working Load Limit	800 LBS
Solution Capacity	120 GAL
Standard Pump Motor Size	5 HP
Standard Pump Capacity	90 GPM @ 60 PSI
Wash Nozzles	12
Turntable Drive - Chain w/"Slip" Lock-up protection	1/15 HP
Vapor Exhaust Stack	6-5/8"
Electric Heat	12 KW
Electric Power Requirement 3 Phase 230V / 460V	3PH 230V-45A / 460V-23A
Fresh Water Inlet x Main Tank Drain Outlet	1/2" NPT x 1" NPT
Weight in Pounds	1,400

STANDARD OPTIONS

Part

Downsize to 3HP 230V 1P/3P Power	140-09
5 HP 230V 1 Phase Power 80A	140-10
7-1/2 HP 230V 3P Power 50A / 460V 3P Power 26A	140-11
7-Day/24-Hour Digital Timer (Heat or Skimmer)	140-20
Auto-Refill with Inlet Strainer & Low-Water Shut-Off	140-21
Evaporation Cycle w/ Separate Heat & Low Shut-Off	140-22
Oil Skimmer 12" SS Disc 60-Min Spring-Wound Timer	140-23
HD Oil Skimmer 12" SS Disc 60-Min Ele. Dial Timer	140-48
15" Small Parts basket	140-25
SS Thermometer - Probe Type	140-26
Stainless Steel Wash Nozzles	140-27
Lower Spray Bar (only w/140-36)	140-28
6" HD Permanent Casters	140-35
Deep Lid (Increases Working Height To 24")	140-36
Hand Detailing Brush w/Pump	140-37
Low-Water Auto Shut-Off	140-38
Bag Filter System #6 x 18 Filter Housing	140-39
** Recirc. Rinse Stage - Stand Alone w/Air Pump, Heat, Auto-Divert	140-44
** Shop Air Blow-Off Cycle	140-45
Vapor Exhaust Fan 120 CFM	140-47
Vapor Exhaust "Mist Scrubber" 3/4 HP 275 CFM	140-48
Wiring Upgrade	140-50
** Digital Cycle Timer (1 req'd per stage)	140-51
** Programmable Relay Control w/Text Display (for mult. stages)	140-51-PR
DEMA Injector (Valve) for adding Rust-Inhibitor or Chemical	140-54
** Powered Lid Gravity-Close, Auto-Open	140-55
Deduction for Non-Powered Turntable w/Positioning Lock	140-56
Pressure Control Valve w/Gauge	140-85

** these options require wiring upgrade part #140-50

Stainless-Steel Construction Available
Many other options available - *Call Us!*

EFFECTIVE 1-JAN-15 SUBJECT TO CHANGE WITHOUT NOTICE
LOCAL CODE REQUIREMENTS ARE THE RESPONSIBILITY OF THE PURCHASER

MANUFACTURER OF HIGH-SPEED INDUSTRIAL PARTS WASHERS